



5KW/15KWH Home Power Storage

All WOCOR Poweray products include CDK-5-15kWh 5KW/15KWH Home Power Storage have been certified to meet regulatory, safety, and environmental standards that meet or exceed market demand. In addition, we are committed to strict quality control, customer service, and reliability that earn the trust of our customers. A home battery and backup system is a great way to

provide clean, eco-friendly energy to your entire home this holiday season and throughout the year. And with modular systems, you can add storage batteries or solar panels as needed to keep up with changing energy needs.

Product Description

If you have a power outage and it looks like the power will be off for an extended period of time, you need backup power from a battery system or battery backup unit like CDK-5-15kWh 5KW/15KWH Home Power Storage. The CDK-5-15kWh 5KW/15KWH Home Power Storage will give you an energy capacity of 15kWh and has a power rating of 15360W. The CDK-5-15kWh 5KW/15KWH Home Power Storage has high cycle times and long life. CDK-5-15kWh 5KW/15KWH Home Power Storage offer recognized green energy, no pollution in the whole production and use process.



Product information		
Model name	CDK-5-15kWh	
Item	General Parameters	Remark
Battery type	Lithium iron phosphate	
Output wave	Pure sine wave	
Rated capacity	100.0Ah	0.2C after standard charging 0.2 C5 standard discharging
Minimum capacity	98.0Ah	
Nominal voltage	5102V	
Expected life	80% of initial capacity	Fistly 0.2C5 constant current charges to 58.4V, then constant voltage charges until current is less than 0.05C
		Set aside:30min
		Discharging :0.2 C5 to 40.0V
		Temperature:20±5℃
		Cycle time 2000 times 100%DOD
End-off discharging voltage	≥32V	40.0V (recommendation)
End-off charging voltage	≤62.4 V	58.4V (recommendation)
Cells connected methods	16S1P	
Casing material	Metal casing	
Standard charging	0.2C constant current charges to 58.4V and constant voltage to 58.4V, charging until the charging current≤0.05C	Charging time:about 6 hours
Standard discharging	Continuous current:0.2C	
	End-off voltage:40.0V	
Maximum charging current	300A	
Maximum continuous	300A	

discharging current		
Peak current	400A	
Working temperature range	Charging: 0~45℃ Discharging: -10~60℃	Recommendation 23±5℃
Storage temperature range	Less than one year: 0~25℃ Less than three months:-10~35℃	Humidity range at shipping state 23 ± 5°
Weight	About 140Kg	
Maximum dimension	Height:240.8cm	
	Width:161.2cm	
	Length:80cm	
Communication	RS485/CAN	Support multiple inverter
Machine in parallel	Support 16 groups n parallel	
Protection function	1.Over charging protection 2.over discharging protection 3.temperature protection 4.over current protection 5.short	
Authentication certificate	CE/FCC/ROSH/PSE/UN3.3/MSDS/Dangerous packing certificate	

Product Feature And Application of the CDK-5-15kWh

- *Working temperature: 0℃-60℃
- * High cycle times and long life
- * High energy density and conversion efficiency
- * Adopt high-performance BMS battery management system
- * There is sufficient insulation safety protection inside the battery
- * Recognized green energy, no pollution in the whole production and use process
- * Specify the specification level according to the national standard or use higher sensitivity standard to ensure the quality of the battery

Operational Process

